

## The IntegriFuse Electrofusion Processor with SmartScan and GPS Technologies



- IntegriFuse Universal Electrofusion equipment, weighing only 56 lbs, is reliable, easy to use, and built with industry leading components that will not overheat.
- An air-tight and water-tight Pelican™ case protects your IntegriFuse EF Processor from outside elements in the most rugged conditions.
- The IntegriFuse Electrofusion Processor will fuse ALL bar coded electrofusion fittings from ½" to 63" and includes pin adapters to fit all North American brands of electrofusion fittings.
- Barcode or Manual entry modes require minimal operator training on the unit.
- The SmartScan barcode wand and optional GPS technology feature faster, more reliable barcode scanning, remote start and stop feature for fusions, and documentation of the GPS location coordinates for all fusions performed.

### Specifications

**Supply Voltage:** 120V AC

**Supply Frequency:** 47 Hz to 70 Hz

**Max Supply Current:** 42 Amps at 80 Amps Output

**Output Voltage:** 8V AC to 48V AC

**Operating Temperature Range:** 15° F to 120° F

**Fusion Information Storage:** 1,000 Fusions

**Power Requirements:** Continuous Watt (non-welding) Generator with 120V power source and 30 Amp twist lock

**Integrity Fusion Products, Inc.**

Phone: 770-632-7530

Fax: 770-632-7540

Info@IntegrityFusion.com