



9” Straw Wattle NN

The 9-inch (22.86 cm) Straw Wattle is an elongated tube of compacted straw and/or other fibers wrapped in 100% biodegradable tubular netting. The 9-inch (22.86 cm) Straw Wattle is used for temporary erosion and sediment control applications and is commonly installed at intervals along the contours or at the base of a slope to help reduce soil erosion and retain sediment. The Straw Wattle is designed to allow runoff/water to penetrate through the fiber while reducing sediment migration. Straw Wattles function as slope interruption devices and therefore shorten slope lengths reducing runoff velocity and the potential for sheet erosion and rill formation. Straw Wattles also provide sediment containment and are used for perimeter sediment control. Straw Wattles work in conjunction with surface roughening, straw mulching, bonded fiber matrix, hydroseeding and erosion control blankets to further reduce erosion and sediment migration.

- The Straw Wattle provides a cost saving 100% biodegradable alternative to typical sediment trapping devices.
- The Straw Wattle can be easily installed and removed or left in place to biodegrade.
- The straw matrix and netting of the 9-inch Straw Wattle is 100% biodegradable.
- The functional longevity is approximately 6-12 months, depending on moisture, light, and environmental conditions.

Property	Test Method	Straw Wattle 9-inch	
		Metric	Imperial
Mass/Unit Length	Field Measure	.84 kg/m ± 10%	1.86 lbs/ft ± 10%
Diameter	Field Measure	22.86 cm	9 in
Length	Field Measure	7.62M	25 ft
Netting Yield	Field Measure	6.2kg/m	12.5 yds/lb

**For Pricing And Availability Contact
Our Sales Team at 780-962-6559**