

Introducing the Padding Bucket Designed Specifically for the Renewable Industry

ALLU Blue Transformer Series (TS) Padding Bucket

Exclusive to Cross Country in the USA for Rentals and Sales

Cross Country and ALLU are proud to announce a padding bucket designed with true 1/2" size to increase productivity on wind and solar farm renewable energy projects.

- » True 1/2" or 12mm sizing for the Renewable Industry
- » Fully contained gel bath for constant lubrication of the gear box including chains and sprockets
- » Paddle configuration for self-cleaning operation

Models and Specifications

MODEL	DN212		DH312-NCD		DH317-NCD		DH417	
	Metric	US units	Metric	US units	Metric	US units	Metric	US units
EXCAVATOR (Metric t / US ton)*	12-28	13-31	18-45	20-50	22-45	24-50	27-45	30-50
WEIGHT WITH ADAPTOR (kg / lbs)*	1,600 kg	3,500 lbs	2,400 kg	5,300 lbs	2,900 kg	6,400 lbs	3,300 kg	7,400 lbs
EXCAVATOR PRESSURE RELIEF SETTING (bar / ksi)	280 bar	4,000 psi	200 bar	3,000 psi	200 bar	3,000 psi	280 bar	4,000 psi
MAX. OPERATION FLOW (l/min / gpm)	160 l/min	42 gpm	220 l/min	58 gpm	220 l/min	58 gpm	315 l/min	83 gpm
OUTPUT SIZE REGULATION	1/2" / 1"		1/2" / 1"		1/2" / 1"		1/2" / 1"	

*All weights are estimated

For Pricing And Availability Contact Us Today at 1-855-955-CCIS (2247)