



Pressure Pump MAC-24

General Description

- Engineered for hydrostatic testing and high-pressure chemical injection applications.
- Features a 4-inch power cylinder and 2-inch stroke
- Lightweight and portable.
- Standard – two fluid ends; optional – single fluid end
- Stroke Counter Available.
- Engineered for hydrostatic testing and high-pressure chemical injection applications.
- 3/8" or 1/2" plungers with 2" stroke.
- Lightweight and portable.
- Skid-mounted system with input regulator, gauge, and valve.
- Standard – two fluid ends; (optional – single fluid end.)
- 35-Gallon Reservoir Tank.
- 1/2" Discharge NPT.



Plunger Size (in.)	Volume - Gallons @ 100 cpm			Operating Pressure	Stall Pressure
	Min.	Hr.	Day		
1/2	0.31	18.36	441	4,325	5,250
3/8	0.17	10.32	689	2,770	3,360

Volume based on 90% theoretical maximum. Stall pressure based on 85% efficiency. Air/Gas consumption @ 100 psi and 100 cpm - 51 SCFM

Shipping Information:

Dimensions		
Shipping Size	43" L x 25" W x 54" H	109.22 cm L x 63.5 cm W x 137.16 cm H
Net Weight	350 lbs.	158.77 kg

Contact Us Today at **1-855-955-CCIS (2247)** or Visit **CrossCountryIS.com**

