



# *StrikeForce EX Hydraulic Breakers*



## Powerful Operations for Maximum Production

Paladin's new Strike Force Breakers provide exceptional performance and reliability for a variety of demolition tasks. From small excavation projects to the toughest demolition jobs, Paladins's Strike Force Breaker series has a smooth, powerful operation for maximum output energy and efficiency.

- » Proven Working Principle
- » Rugged Construction
- » Wide Range of Models
- » Easy Service & Maintenance



**For Pricing And Availability  
Contact Our Sales Team at 1-855-955-CCIS (2247)**

# Compact and Small Mounted Breakers



Specifications	Units	SFB250	SFB350	SFB500	SFB750	SFB1000	SFB1500
Working Weight	(lbs)	298	414	532	650	959	1243
Impact Energy Class	(ft. lbs.)	250	350	500	750	1000	1500
"Impact Rate (BPM)"	-	700~1500	450~1150	640~1470	620~1150	450~750	400~750
Operating Pressure	(psi)	1305~1740	1305~1885	1595~2117	1566~2175	1377~1880	1800~2175
Relief Pressure	(psi)	2320~2610	2320~2610	2320~2610	2320~2610	2320~2610	2320~2610
Oil Flow Range	(gal/min)	4.0~9.2	6.6~11.9	10.0~21.9	11.9~21.9	10.6~21.1	11.9~22.5
Tool Diameter	(in)	1.57	2.15	2.63	2.67	2.93	3.32
Pressure Line Size	(mm (in))	12 (½)	12 (½)	19 (¾)	19 (¾)	12 (½)	19 (¾)
Return Line Size	(mm (in))	12 (½)	12 (½)	19 (¾)	19 (¾)	12 (½)	19 (¾)
Carrier Weight	(lbs)	2204~6614	4409~9921	5070~13227	7054~15873	9921~19842	15432~26455
Machine Class	(mT)	0-3	2-5	3-5	3-8	5-8	8-12

# Medium and Large Range Breakers



Specifications	Units	SFB2K	SFB3K	SFB4K	SFB5K	SFB6K	SFB8K	SFB10K	SFB12K
Working Weight	(lbs)	2209	3142	4105	4738	5833	6263	7301	9259
Impact Energy Class	(ft. lbs.)	2000	3000	4000	5000	6000	8000	10000	12000
"Impact Rate (BPM)"	low speed	400-600	350~500	350~500	350~450	300~400	300~400	250~350	200~350
"Impact Rate (BPM)"	high speed	550-750	450~650	450~600	400~500	350~450	350~450	300~400	300~400
Operating Pressure	(psi)	2030-2320	2175~2465	2320~2610	2320~2610	2320~2610	2320~2610	2320~2610	2320~2610
Relief Pressure	(psi)	2755-2900	2755~2900	2900~3045	2900~3045	2900~3045	2900~3045	2900~3045	2900~3045
Oil Flow Range	(gal/min)	21.1-29	23.8~31.7	26.4~39.6	31.7~47.6	39.6~55.5	47.6~63.4	52.8~68.7	66.0~79.3
Tool Diameter	(in)	3.9	4.88	5.27	5.46	5.85	6.05	6.44	7.1
Pressure Line Size	(mm (in))	19 (¾)	25 (1)	25 (1)	25 (1)	25 (1)	32 (1¼)	32 (1¼)	32 (1¼)
Return Line Size	(mm (in))	19 (¾)	25 (1)	25 (1)	25 (1)	25 (1)	32 (1¼)	32 (1¼)	32 (1¼)
Carrier Weight	(lbs)	24251-35274	28660-39683	35274-46297	39683-57320	55116-66139	61729-77162	66139-99208	88145-121254
Machine Class	(mT)	10-12	12-15	15-20	15-25	25-27	27-35	27-45	35-45